PR402.TXT

MATERIAL SAFETY DATA SHEET

PROTECTO COPP Page:

PRODUCT NAME: PROTECTO COPP HMIS CODES: H F R P

PRODUCT CODE: PR-402 3 2 0 H

======= SECTION I - MANUFACTURER IDENTIFICATION ===========

MANUFACTURER'S NAME: LANCO MFG. CORP. : URB. APONTE #5

SAN LORENZO, PUERTO RICO

00754

: (787) 736-4200 DATE PRINTED : 12/05/02 **EMERGENCY PHONE**

INFORMATION PHONE : (787) 736-4200 NAME OF PREPARER: LANCO MFG.CORP.

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

VAPOR PRESSURE WEIGHT REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP PERCENT

ALIPHATIC SOLVENT 64742-88-72

OSHA PEL: 500 PPM, ACGIH TLV: 100 PPM, OTHER: N/A

1338-02-9 2.6 68 F 11.2 COOPER NAPHTHENATE

ACGIH TLV 525 mg/m3

OSHA PEL TWA 100 ppm M.SPIRIT

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

======= SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ========

SPECIFIC GRAVITY (H2O=1): BOILING RANGE: 300 deg F - 315-385 F VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER COATING V.O.C.: 6.14 lb/gl MATERIAL V.O.C.: 5.95 lb/gl

SOLUBILITY IN WATER: NON SOLUBLE APPEARANCE AND ODOR: SOLVENT ODOR

======= SECTION IV - FIRE AND EXPLOSION HAZARD DATA =========

FLASH POINT: 104 deg F METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.3 UPPER: 14.4

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

RESPIRATORY EQUIPMENT SHOULD BE WORN TO AVOID INHALATION OF CONCENTRATED VAPOR.WATER SHOULD NOT BE USED EXCEPT AS FOG TO KEEP NEARBY CONTAINERS COOL.

UNUSUAL FIRE AND EXPLOSION HAZARDS

EXTREMELY FLAMMABLE. VAPORS MAY IGNITE EXPLOSIVELY AND/OR CAUSE FLASH FIRES. ELIMINATE SOURCES OF IGNITION. NO SMOKING. USE ADEQUATE CROSS VENTILATION SUFFICIENT TO REMOVE ODOR OF SOLVENT AND VAPORS.

STABILITY: STABLE CONDITIONS TO AVOID

EXCESSIVE HEAT, POOR VENTILATION, CORROSIVE ATMOSPHERES, EXCESSIVE AGING.

INCOMPATIBILITY (MATERIALS TO AVOID)

STRONG OXIDIZING AGENTS, STRONG ACIDS AND OXIDIZING MATERIALS, ALKALINE MATERIALS.

PR402.TXT

2

HAZARDOUS DECOMPOSITION OR BYPRODUCTS CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

MATERIAL SAFETY DATA SHEET

PROTECTO COPP Page:

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

======== SECTION VI - HEALTH HAZARD DATA =============

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE ACUTE SIGNS OF OVEREXPOSURE COULD BE HEADACHE, DIZZINESS NAUSEA, UPPER RESPIRATORY DRYNESS OR IRRITATION, DROWSINESS, MENTAL DEPRESSION OR NARCOSIS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE EYE CONTACT: SEVERE IRRITATION, TEARING, REDNESS AND BLURRED VISION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE SKIN CONTACT: CAN DRY AND DEFEAT SKIN CAUSING CRACKS, IRRITATION, AND DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC) INHALATION-DIZZYNESS, BREATHING DIFFICULTY, HEADACHES, LOSS OF COORDINATION. EYE CONTACT-SEVERE IRRITATION, TEARING, REDNESS, AND BLURRED VISION. SKIN CONTACT-CAN DRY AND DEFEAT SKIN CAUSING CRACKS, IRRITATION AND DERMITITIS. INGESTION-CAN CAUSE GASTROINTESTINAL IRRITATION, VOMITING NAUSEA, DIARRHEA. NO CHRONIC HEALTH EFFECTS.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE ANESTHESIA, RESPIRATORY TRACT IRRITATION, DERMITITIS, NAUSEA, VOMITING.

EMERGENCY AND FIRST AID PROCEDURES INHALATION OVEREXPOSURE - MOVE PERSON TO FRESH AIR. IF BREATHING STOPS, APPLY ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATENTION. EYE CONTACT- FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES. SKIN CONTACT- WASH THOROUGHLY WITH SOAP AND WATER AND SEE A DOCTOR. INGESTION DO NOT INDUCE VOMITING, CAN CAUSE CHEMICAL PHEUMONITIS AND PULMONARY EDEMA. CONTACT PHYSICAL IMMEDIATELY.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED REMOVE SOURCES OF IGNITIONS, PROVIDE GOOD VENTILATION, DIKE SPILL AREA ADD ABSORBENT EARTH OR SAWDUST TO SPILLED LIQUID. THOROGHLY WET W/ WATER AND MIX.

WASTE DISPOSAL METHOD COLLECT ABSORBENT/ WATER/ SPILLED LIQUID MIXTURE INTO METAL CONTAINERS AND ADD ENOUGH WATER TO COVER. CONSULT LOCAL, STATE & FEDERAL HAZARDOUS WASTE REGULATION BEFORE DISPOSING INTO APPROVED HAZARDOUS WASTED LANDFILLS. OBEY RELEVANT LAW.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING KEEP CONTAINERS CLOSED WHEN NOT IN USE. STORE 60-95 F OUT OF SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOR WHEN COVER REMOVED. KEEP AWAY EXESSIVE HEAT AND OPEN FLAMES.

OTHER PRECAUTIONS

GROUND ALL EQUIPMENT WHEN HANDLING FLAMMABLE SOLVENT BORNE MATERIALS. SMOKING IN AREA WHERE THIS MATERIAL IS USED SHOULD BE STRICTLY PROHIBITED.

PR402.TXT

RESPIRATORY PROTECTION

WHEN SPRAYING THIS MATERIAL USE A NIOSH APPROVED CARTRIDGE RESPIRATOR OR GAS MASK SUITABLE TO KEEP AIRBORNE MISTS AND VAPOR CONCENTRATIONS BELOW THE TIME M A T E R I A L S A F E T Y D A T A S H E E T

PROTECTO COPP Page: 3

WEIGHTED THRESHOLD LIMIT VALUES. WHEN USING IN POORLY VENTILATED AND CONFINED SPACES, USE A FRESH-AIR SUPPLYING RESPIRATOR OR A SELF- CONTAINED BREATHING APPARATUS.

VENTILATION

SUFFICIENT TO KEEP WORKROOM CONCENTRATION BELOW TLV. VENTILATION EQUIP. MUST BE EXLPOSION PROOF.

PROTECTIVE GLOVES
CHEMICALS RESISTANT GLOVES.

EYE PROTECTION

USE CHEMICAL SAFETY GLASSES, GOGGLES, AND FACESHIELDS FOR EYE PROTECTION.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

USE IMPERMEABLE APRONS AND PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT SKIN CONTACT. THE USE OF HEAD CAPS WHENEVER POSSIBLE IS STRONGLY RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE IS RECOMMENDED.

The information contained herein is based on data believed by this company to be accurate, but we do not assume any liability for its accuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsibility of the user.